

- ❑ Catalog number – **H-11175**†
- ❑ Sizes* – 1/2", 1/2" x 3/4"**, 3/4", 1", 1-1/4", 1-1/2", 2"
- ❑ Meets the test requirements specified in ASME B16.33
- ❑ Iron body valve
- ❑ Lockwing head
- ❑ Special lubrication system---can be re-lubricated under pressure
- ❑ O-ring sealed key
- ❑ Tamperproof feature
- ❑ Inlet and outlet with internal I.P. (F.I.P.) thread
- ❑ Available finishes: black (as cast), galvanized, electro-coat epoxy gray, electro-coat Rustoleum gray
- ❑ 175 psig (1208 kPa)
- ❑ Available with 1/8" test port feature



H-11175

Optional Equipment



H-11199

H-11199 Relubricating Tool

Used to relubricate Mueller Luboseal Meter Valves with H-853 lubricant shown below. A hex wrench is built into the tool handle for removal of valve lubricating port pipe plug. One tool fits all valve sizes.



H-853


H-853 Ground Key Lubricant

Used for dry, natural or manufactured gas, air and vacuum applications. NOT recommended for petroleum solvents, mineral oils or concentrated acids or alkalies.

Box of 24 #1 sticks

H-11175 Mueller Luboseal Meter Valve Dimensions

| Dimension | Valve Size** | | | | | | |
|-----------|--------------|---------------------|----------|-----------|---------------|---------------|-----------|
| | 1/2" | 1/2" x 3/4"*** | 3/4" | 1" | 1-1/4" | 1-1/2" | 2" |
| A | 1/2"-14 | 1/2"-14x 3/4"-14 | 3/4"-14 | 1"-11-1/2 | 1-1/4"-11-1/2 | 1-1/2"-11-1/2 | 2"-11-1/2 |
| B | 1-1/2" | 1-29/32" | 1-29/32" | 2-15/64" | 2-43/64" | 3-7/64" | 3-41/64" |
| C | 2-13/16" | 3-5/32" | 3-5/32" | 3-13/16" | 4-1/4" | 4-5/8" | 5-9/32" |
| D | 1-13/32" | 1-37/64" | 1-37/64" | 1-29/32" | 2-1/8" | 2-5/16" | 2-41/64" |
| E | 1-37/64" | 1-31/32" | 1-31/32" | 2-5/32" | 2-9/16" | 2-11/16" | 3-17/64" |
| F | 1-9/32" | 1-39/64" | 1-39/64" | 1-57/64" | 2-3/16" | 2-35/64" | 2-31/32" |
| G | 3/4" | 59/64" | 59/64" | 1-11/64" | 1-27/64" | 1-19/32" | 1-29/32" |



*First size is size of inlet, second is size of outlet

**Nominal

†All meter valves are sold in complete box quantity only.